

# SHOW COOKING (Gas wall of flames)

## US LEGEND range : tradition and performance

>> *Butchers, restaurants, supermarkets and hypermarkets*

Finish with enamelled front panels \* ● ● ●

Indoor and outdoor use



- 3 colours Red, Black and Blue (other colours under request).
- Finishing stainless steel or brass trim.
- Delivered with glass door and spits with claws.
- Capacity per spit : 6 chickens of  $\pm$  1,2 kg.
- Adjustment of the spits depths allowing the roasting of different sizes of meat.
- One motor per spit.
- Halogen lamp 300 watts.
- Electric spark ignition.
- Entirely stainless steel made.
- Option to be mentioned at the order: vertical spit with motorization.
- Pressure regulator set not provided.
- Heating zone : 1012 mm
- Power supply 230 Volts 50Hz single phase.

GLASS DOOR  
INCLUDED



**ITLUF4 + ITPLUR390T**  
Photos are for guidance only



*Our teams developed especially for you, the ideal package for your daily cooking, in the optimized conditions of use, in terms of ergonomics, design and safety*

## US LEGEND : OUR CONSULTING PACKAGE

### Pack LA composed of :

- > a rotisserie equipped with 4 spits with claws (ITLUF4),
- > a cabinet height 900 mm (ITPLUR390T),
- > an universal spit (ITRBULU).

Set dimensions : 1580 x 885 x 2020 mm

### Options :

- > Natural gas connection : 2085TU2015 + 2085PUF20 (See page 41)
- > Propane gas connection : ITAKGP03 (See page 41)

For an outdoor use, we advise  
you to put a roof



### OUR OTHER PACKAGES :

#### **ELECTRIC package**

> See page 30

#### **MUST package**

> See page 8 « Seduction »

#### **ECO package**

> See page 22 « Comfort Plus »

# SHOW COOKING (Gas wall of flames)

## US LEGEND range : tradition and performance

>> *Butchers, restaurants, supermarkets and hypermarkets*

### MODELS

Recommendations and installation : see pages 42-43



Number of spits	L x D x H mm	kW	kg	Ref.
4	1580 x 750 x 1120	30	216	<b>ITLUFR4</b>
6	1580 x 750 x 1570	45	324	<b>ITLUFR6</b>
8	1580 x 750 x 2020	60	432	<b>ITLUFR8</b>

### OPTIONS

Designation	Ref.
<b>REMOVABLE FLAT TOP</b>	<b>ITLEUL</b>
<b>4 CASTORS ALONE - Ø 125 mm height 165 mm (2 with brakes)</b>	<b>SEITRSX</b>
















UNDERFRAME ON CASTORS	L x D x H mm	Ref.
<b>Height 440 mm</b>	1550 x 755 x 400	<b>ITPLUR240</b>
<b>Height 750 mm with an unspitting drawer + 1 tray</b>	1550 x 825 x 750	<b>ITPLUR275T</b>
<b>Height 900 mm with an unspitting drawer + 1 tray</b>	1550 x 825 x 900	<b>ITPLUR290T</b>



STAINLESS STEEL CABINET WITH 2 DOORS ON CASTORS	L x D x H mm	Ref.
<b>Height 750 mm with an unspitting drawer + 1 tray</b>	1550 x 885 x 750	<b>ITPLUR375T</b>
<b>Height 900 mm* with an unspitting drawer + 1 tray</b>	1550 x 885 x 900	<b>ITPLUR390T</b>

\* cabinet can house gas supply cylinders

### ACCESSORIES (see details page 16)

Designation	Useful length mm	Ref.
 <b>Intermediary drip tray</b>		<b>SEITLU180</b>
 <b>Simple spit with claws</b>	1040	<b>ENITRBLU</b>
 <b>Sword spit</b>	1040	<b>ITRBPLU</b>
 <b>Spit for roast</b>	960	<b>ITRBHLU</b>
 <b>Universal basket spit</b>	960	<b>ITRBULU</b>
 <b>Spit for suckling pigs Ø 200</b>	960	<b>ITRBCOLU</b>
 <b>Spit for potatoes</b>	960	<b>ITRBQLU</b>
 <b>Vertical spit with 6 hooks and motorization + 3 leg of lamb spits + 3 quail spits + 1 plate with 4 hooks + 3 " S " hooks</b>		<b>ENITLU44BV</b>
 <b>Leg of lamb spit</b>		<b>SEITM625</b>
 <b>Quail spits</b>		<b>SEITM640</b>
 <b>Spit for chitterlings</b>		<b>3080ITM645</b>
 <b>Plate with 4 hooks</b>		<b>SEITM623</b>
 <b>" S " hook</b>		<b>3080ITM630</b>
<b>Support to unspit</b>		<b>ITAPB</b>

For installations with propane gas, we advise you to add the spareparts (gas connexions, links ...), page 41.