



TECHNICAL DATA	STD		
EXTERNAL DIMENSIONS			
width	590 mm		
depth	600 mm		
height	850 mm		
WEIGHT	56,5 kg		
VOLTAGE	400V 3N 50Hz		
POWER REQUIRED	5150 W		
WATER HARDNESS	2-8 °F		
INLET WATER PRESSURE	200-400 kPa		
CROCKERY DIMENSIONS			
plates diameter	345 mm		
dishes max. height	320 mm		
RACK DIMENSIONS	500X500 mm		
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060		
WASHING CYCLES (sec)	1(90)	2(120)	3(180)
WATER SUPPLY 55°C			
racks/h/>(*)(¹)	40	30	20
WATER SUPPLY 10°C			
racks/h/>(*)(¹)	20	20	20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 L		
BOILER CAPACITY	5.7 L		
BOILER HEATING ELEMENT	4500 W		
RINSING TEMPERATURE (SET)	85°C		
TANK CAPACITY	29 L		
TANK HEATING ELEMENT	2700 W		
TANK TEMPERATURE (SET)	55°C		
PUMP POWER	650 W (340 L/min ^{***})		
DRAIN PUMP (optional)	25 W h MAX drainig 0.8m (40 L/min ^{***})		
NOISE	63 dB(A)		

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.