



	<b>WATER CONNECTION 3/4" GAS</b>
	<b>DRAINING PIPE Ø 24mm</b>
	<b>ELECTRICAL SUPPLY</b>

TECHNICAL DATA	
<b>EXTERNAL DIMENSIONS</b>	
width	590 mm
depth	600 mm
height	1290 mm
<b>WEIGHT</b>	68.5 kg
<b>VOLTAGE</b>	400V 3N 50Hz
<b>POWER REQUIRED</b>	6900 W
<b>WATER HARDNESS</b>	2-8 °F
<b>INLET WATER PRESSURE</b>	200-400 kPa
<b>CROCKERY DIMENSIONS</b>	
plates diameter	380 mm
dishes max. height	355 mm
<b>RACK DIMENSIONS</b>	500X500 mm
<b>RACK EQUIPMENT</b>	1XC40 - 1XC44 - 1X15060
<b>WASHING CYCLES</b> (sec)	1 (90)      2 (180)
<b>WATER SUPPLY 55°C</b>	
racks/h <sup>(*)</sup> ( <sup>1</sup> )	40      20
<b>WATER SUPPLY 10°C</b>	
racks/h <sup>(*)</sup> ( <sup>1</sup> )	26      20
<b>WATER CONSUMPTION / CYCLE</b> (water pressure 200kPa)	2.3 L
<b>BOILER CAPACITY</b>	5.7 L
<b>BOILER HEATING ELEMENT</b>	6000 W
<b>RINSING TEMPERATURE (SET)</b>	85°C
<b>TANK CAPACITY</b>	29 L
<b>TANK HEATING ELEMENT</b>	2700 W
<b>TANK TEMPERATURE (SET)</b>	55°C
<b>PUMP POWER</b>	900 W (500 L/min <sup>***</sup> )
<b>DRAIN PUMP (optional)</b>	25 W h MAX drainig 0.8m (40 L/min <sup>***</sup> )
<b>NOISE</b>	63 dB(A)

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.